

SAFETY DATA SHEET Technolube ATF-Q Transmission Fluid

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Technolube ATF-Q Transmission Fluid

Product number ADQ010,ADQ025,ADQ455

Internal identification O-NC

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Supplier A1 MOTOR STORES LIMITED

Unit 20 Waterfield Way Sketchley Meadows Ind Est

Hinckley Leicestershire LE10 3ER

Tel: 01455 895904 Fax: 01455 631646

Manufacturer TETROSYL LIMITED

Bury Lancashire England BL9 7NY

0161 764 5981 0161 797 5899 info@tetrosyl.com

1.4. Emergency telephone number

Emergency telephone 0161 764 5981

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Not Classified

Health hazards Elicitation - EUH208

Environmental hazards Aquatic Chronic 3 - H412

2.2. Label elements

Hazard statements H412 Harmful to aquatic life with long lasting effects.

EUH208 Contains 2-PROPANOL, 1-(TERT-DODECYLTHIO)-. May produce an allergic

reaction.

Technolube ATF-Q Transmission Fluid

Precautionary statements P273 Avoid release to the environment.

P501 Dispose of contents/container in accordance with national regulations. P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT

1-5%

NAPHTHENIC. <3% DMSO EXTRACT

CAS number: 64742-53-6 EC number: 265-156-6

Classification Classification (67/548/EEC or 1999/45/EC)

Asp. Tox. 1 - H304 Xn;R65.

2-PROPANOL, 1-(TERT-DODECYLTHIO)-

<1%

Classification Classification (67/548/EEC or 1999/45/EC)

Skin Sens. 1 - H317 N;R50/53. R43.

Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

TOLUENE <1%

CAS number: 108-88-3 EC number: 203-625-9 REACH registration number: 01-

2119471310-51-XXXX

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Liq. 2 - H225 F;R11 Repr. Cat. 3;R63 Xn;R48/20,R65 Xi;R38 R67

Skin Irrit. 2 - H315 Repr. 2 - H361d STOT SE 3 - H336 STOT RE 2 - H373 Asp. Tox. 1 - H304

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Get medical attention if any discomfort continues. Remove affected person from source of

contamination. Move affected person to fresh air and keep warm and at rest in a position

comfortable for breathing.

Inhalation If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and

keep warm and at rest in a position comfortable for breathing.

Ingestion Contact physician if larger quantity has been consumed. Rinse mouth thoroughly with water.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Get medical

attention if irritation persists after washing.

Technolube ATF-Q Transmission Fluid

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 15 minutes. Do not rub eye.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure. Effects may be delayed. Keep affected person under observation.

Inhalation May cause an asthma-like shortness of breath. Vapours may cause headache, fatigue,

dizziness and nausea.

Ingestion May cause discomfort if swallowed. May cause stomach pain or vomiting. May cause nausea,

headache, dizziness and intoxication.

Skin contact Prolonged or repeated contact with skin may cause irritation, redness and dermatitis. Allergic

rash

Eye contact May cause temporary eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Foam, carbon dioxide or dry powder. Use fire-

extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Fire creates: Carbon monoxide (CO). Carbon dioxide (CO2). No unusual fire or explosion

hazards noted.

Hazardous combustion

products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or

vapours. Oxides of carbon.

5.3. Advice for firefighters

Special protective equipment

for firefighters

Leave danger zone immediately.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Follow precautions for safe handling described in this safety data sheet. Avoid inhalation of

vapours. Avoid contact with eyes and prolonged skin contact. Provide adequate ventilation. In

case of spills, beware of slippery floors and surfaces.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. Collect and dispose of

spillage as indicated in Section 13.

6.3. Methods and material for containment and cleaning up

Technolube ATF-Q Transmission Fluid

Methods for cleaning up

Stop leak if possible without risk. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Provide adequate ventilation. Contain spillage with sand, earth or other suitable non-combustible material. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. Collect and

dispose of spillage as indicated in Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Good personal hygiene procedures should be implemented. Wash hands and any other

contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product. Avoid the formation of mists. Provide adequate ventilation. Avoid contact with skin and eyes. Always remove oil with soap and water or skin cleaning agent, never use organic solvents. Do not use oil-contaminated clothing or shoes,

and do not put rags moistened with oil into pockets.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep containers upright. Store in tightly-closed, original container.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

No exposure limits known for ingredient(s).

TOLUENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 191 mg/m³ Short-term exposure limit (15-minute): WEL 100 ppm 384 mg/m³ Sk

WEL = Workplace Exposure Limit Sk = Can be absorbed through skin.

8.2. Exposure controls

Protective equipment







Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Technolube ATF-Q Transmission Fluid

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if

a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. It should be noted that liquid may penetrate the gloves.

Frequent changes are recommended.

Other skin and body

protection

Wear suitable protective clothing as protection against splashing or contamination.

Hygiene measures Wash contaminated clothing before reuse. Wash promptly with soap and water if skin

becomes contaminated.

Respiratory protection No specific recommendations.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Clear liquid.

Colour Red.

Odour Oil-like.

Odour threshold Scientifically unjustified. Scientifically unjustified.

pH Scientifically unjustified.

Melting point Scientifically unjustified.

Initial boiling point and range >250°C @

Flash point 215°C

Evaporation rate Scientifically unjustified.

Upper/lower flammability or

explosive limits

Scientifically unjustified.

Vapour pressure Scientifically unjustified.

Vapour density Scientifically unjustified.

Relative density 0.870 g/cm³ @ 20°C

Solubility(ies) Insoluble in water.

Partition coefficient Scientifically unjustified.

Auto-ignition temperature Scientifically unjustified.

Decomposition Temperature Scientifically unjustified.

Viscosity 37 cSt @ 40°C

Oxidising properties Not determined.

9.2. Other information

Other information None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability No particular stability concerns.

Technolube ATF-Q Transmission Fluid

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

products

Not applicable.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition

Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects No information available.

Skin contact Prolonged and frequent contact may cause redness and irritation.

Eye contact May cause temporary eye irritation.

SECTION 12: Ecological Information

Ecotoxicity Not regarded as dangerous for the environment.

12.1. Toxicity

Acute toxicity - fish Not determined.

Acute toxicity - aquatic

invertebrates

Not determined.

Acute toxicity - aquatic plants Not determined.

12.2. Persistence and degradability

Persistence and degradability No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Scientifically unjustified.

12.4. Mobility in soil

Mobility The product is insoluble in water.

Adsorption/desorption

coefficient

Not available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects Not available.

Technolube ATF-Q Transmission Fluid

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in

accordance with the requirements of the local Waste Disposal Authority.

Disposal methodsConfirm disposal procedures with environmental engineer and local regulations.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18

December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date 20/07/2015

Revision 0

Technolube ATF-Q Transmission Fluid

SDS number 31368

SDS status Approved.

Risk phrases in full Not classified.

R36 Irritating to eyes.

Hazard statements in full H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways. H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H336 May cause drowsiness or dizziness. H361d Suspected of damaging the unborn child.

H361f Suspected of damaging fertility.

H361fd Suspected of damaging fertility. Suspected of damaging the unborn child. H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

EUH208 Contains 2-PROPANOL, 1-(TERT-DODECYLTHIO)-. May produce an allergic

reaction.